

PostgreSQL9.3 パラメータ反映のタイミング

| 反映のタイミング | |
|---------------|--------------------------|
| DBの再起動が必用 | ビルドもしくはDB初期化時に設定可能 |
| | DBの再起動時に反映可能 |
| DBを再起動せずに反映可能 | リロード(pg_ctl reload)で反映可能 |

セッション開設時に反映可能

superuserがDBセッション内で変更可能

ユーザがDBセッション内で変更可能

| | |
|--|--|
| | |
|--|--|

| パラメータ |
|--------------------------------|
| block_size |
| integer_datetimes |
| lc_collate |
| lc_ctype |
| max_function_args |
| max_identifier_length |
| max_index_keys |
| segment_size |
| server_encoding |
| server_version |
| server_version_num |
| wal_block_size |
| wal_segment_size |
| allow_system_table_mods |
| archive_mode |
| autovacuum_freeze_max_age |
| autovacuum_max_workers |
| bonjour |
| bonjour_name |
| config_file |
| data_directory |
| external_pid_file |
| hba_file |
| hot_standby |
| ident_file |
| listen_addresses |
| logging_collector |
| max_connections |
| max_files_per_process |
| max_locks_per_transaction |
| max_pred_locks_per_transaction |
| max_prepared_transactions |
| max_wal_senders |
| pg_stat_statements.max |
| port |
| shared_buffers |
| shared_preload_libraries |
| silent_mode |
| ssl |
| ssl_ciphers |
| superuser_reserved_connections |
| track_activity_query_size |
| unix_socket_directory |
| unix_socket_group |
| unix_socket_permissions |
| wal_buffers |
| wal_level |
| archive_command |
| archive_timeout |

| |
|---------------------------------|
| authentication_timeout |
| autovacuum |
| autovacuum_analyze_scale_factor |
| autovacuum_analyze_threshold |
| autovacuum_naptime |
| autovacuum_vacuum_cost_delay |
| autovacuum_vacuum_cost_limit |
| autovacuum_vacuum_scale_factor |
| autovacuum_vacuum_threshold |
| bgwriter_delay |
| bgwriter_lru_maxpages |
| bgwriter_lru_multiplier |
| checkpoint_completion_target |
| checkpoint_segments |
| checkpoint_timeout |
| checkpoint_warning |
| custom_variable_classes |
| db_user_namespace |
| deadlock_timeout |
| fsync |
| full_page_writes |
| hot_standby_feedback |
| krb_caseins_users |
| krb_server_keyfile |
| krb_srvname |
| log_autovacuum_min_duration |
| log_checkpoints |
| log_destination |
| log_directory |
| log_file_mode |
| log_filename |
| log_hostname |
| log_line_prefix |
| log_rotation_age |
| log_rotation_size |
| log_timezone |
| log_truncate_on_rotation |
| max_standby_archive_delay |
| max_standby_streaming_delay |
| pg_stat_statements.save |
| pre_auth_delay |
| replication_timeout |
| restart_after_crash |
| stats_temp_directory |
| synchronous_standby_names |
| syslog_facility |
| syslog_ident |
| trace_recovery_messages |
| vacuum_defer_cleanup_age |
| wal_keep_segments |
| wal_receiver_status_interval |
| wal_sender_delay |

| |
|----------------------------------|
| wal_sync_method |
| wal_writer_delay |
| ignore_system_indexes |
| local_preload_libraries |
| log_connections |
| log_disconnections |
| post_auth_delay |
| dynamic_library_path |
| lc_messages |
| lo_compat_privileges |
| log_duration |
| log_error_verbosity |
| log_executor_stats |
| log_lock_waits |
| log_min_duration_statement |
| log_min_error_statement |
| log_min_messages |
| log_parser_stats |
| log_planner_stats |
| log_statement |
| log_statement_stats |
| log_temp_files |
| max_stack_depth |
| pg_stat_statements.track |
| pg_stat_statements.track_utility |
| session_replication_role |
| track_activities |
| track_counts |
| track_functions |
| update_process_title |
| zero_damaged_pages |
| DateStyle |
| IntervalStyle |
| TimeZone |
| application_name |
| array_nulls |
| backslash_quote |
| bytea_output |
| check_function_bodies |
| client_encoding |
| client_min_messages |
| commit_delay |
| commit_siblings |
| constraint_exclusion |
| cpu_index_tuple_cost |
| cpu_operator_cost |
| cpu_tuple_cost |
| cursor_tuple_fraction |
| debug_assertions |
| debug_pretty_print |
| debug_print_parse |
| debug_print_plan |

| |
|--------------------------------|
| debug_print_rewritten |
| default_statistics_target |
| default_tablespace |
| default_text_search_config |
| default_transaction_deferrable |
| default_transaction_isolation |
| default_transaction_read_only |
| default_with_oids |
| effective_cache_size |
| effective_io_concurrency |
| enable_bitmapscan |
| enable_hashagg |
| enable_hashjoin |
| enable_indexscan |
| enable_material |
| enable_mergejoin |
| enable_nestloop |
| enable_seqscan |
| enable_sort |
| enable_tidscan |
| escape_string_warning |
| exit_on_error |
| extra_float_digits |
| from_collapse_limit |
| geqo |
| geqo_effort |
| geqo_generations |
| geqo_pool_size |
| geqo_seed |
| geqo_selection_bias |
| geqo_threshold |
| gin_fuzzy_search_limit |
| join_collapse_limit |
| lc_monetary |
| lc_numeric |
| lc_time |
| maintenance_work_mem |
| password_encryption |
| quote_all_identifiers |
| random_page_cost |
| search_path |
| seq_page_cost |
| sql_inheritance |
| ssl_renegotiation_limit |
| standard_conforming_strings |
| statement_timeout |
| synchronize_seqscans |
| synchronous_commit |
| tcp_keepalives_count |
| tcp_keepalives_idle |
| tcp_keepalives_interval |
| temp_buffers |

| |
|-------------------------|
| temp_tablespaces |
| timezone_abbreviations |
| trace_notify |
| trace_sort |
| transaction_deferrable |
| transaction_isolation |
| transaction_read_only |
| transform_null_equals |
| vacuum_cost_delay |
| vacuum_cost_limit |
| vacuum_cost_page_dirty |
| vacuum_cost_page_hit |
| vacuum_cost_page_miss |
| vacuum_freeze_min_age |
| vacuum_freeze_table_age |
| work_mem |
| xmlbinary |
| xmloption |